



PRODUCT DETAILS

Product Name:	Jax Gilders Paste
Product Description:	A wax based paste with pigment
Areas of Application:	Any surface that requires a special effect or added colour
Substrate Material:	N/A

SURFACE PREPARATION

Surface Preparation:	Clean and dry before applying
Substrate Sanding Grits:	N/A
Comments on Sanding:	N/A

APPLICATION

Airless:	N/A
Airless low pressure:	N/A
Airmix:	N/A
Compressed air spaying:	N/A
Wiping sponge roller:	Yes
Non-wiping sponge roller:	Yes
Expel with brush/paintbrush:	N/A
Smooth Roller:	Yes
Spreading:	Yes

TECHNICAL DATA

Yield per coat:	Dependant of thickness applied
Flow time (+/- 15%):	N/A
Proportion of renewable raw material:	0
Non-volatile proportion:	1
Conditions of transport:	Under 20 °C as the paste will soften
VOC:	0
Shelf life:	1 year
Number of coats (max):	As desired
Amount per layer (minimum):	5 ml/m ²
Amount per layer (max):	15ml/m ²
Total application volume:	0
Drying:	Dries immediately, if not in liquid form
Finishing:	N/A
Sealing:	Can be sealed with any of our sealers.

PROCESSING & SPECIAL NOTES

Processing Instructions:	Apply as required to achieve the effect. Can be thinned out with turps. If the product is dry, add turps.
Particular Instructions:	0

GENERAL WORKMANSHIP NOTES

General Instruction on Workmanship:	Apply with a brush or soft cloth, use turps to thin and clean.
-------------------------------------	--

Our technical information is continually adapted to keep up to date with the latest technology and statutory regulations. The indicated values are no specification, but typical product data. The latest version is always available online at www.jaxoleum.co.za or talk to your local account manager. This information is for advice and is based on the best knowledge available and careful research in line with the current state of the art. This information cannot be held as legally binding. We also refer you to our terms and conditions of business. Material safety data sheet is provided in accordance with EC regulation no. 1907/2006.