

TECHNICAL DATA SHEET



PRODUCT DETAILS

Product Name:	Jax Oleum
Product Description:	Single Coat oil-based wood stain that protects, nourishes and colours wood in one easy application
Areas of Application:	Any prepared timber surface, indoor or outdoor
Substrate Material:	• Any timber product • Dark, fine pored hardwood • dark deciduous woods with coarse pores • light deciduous woods with fine pores • light deciduous woods with coarse pores

SURFACE PREPARATION

Surface Preparation:	The wood must be dry, dust-free and grease-free and evenly sanded before applying any Jax Oleum
Substrate Sanding Grits:	120 is recommend but can go up to 240.
Comments on Sanding:	Ensure all previous sealers/varnishes/coats are fully removed by even sanding. The smoother the timber the less absorption of the Jax Oleum.

APPLICATION

Airless:	Yes
Airless low pressure:	No
Airmix:	No
Compressed air spraying:	No
Wiping sponge roller:	No sponge
Non-wiping sponge roller:	No sponge
Expel with brush/paintbrush:	Yes
Smooth Roller:	No
Spreading:	Yes, preferred method with a soft cloth

TECHNICAL DATA

Yield per coat:	20-50 m ² per litre depending on the wood species and preparation there of
Flow time (+/- 15%):	N/A
Proportion of renewable raw material:	0
Non-volatile proportion:	0,45
Conditions of transport:	Under 140 °C
VOC:	A
Shelf life:	5 years
Number of coats (max):	1
Amount per layer (minimum):	15ml/m ²
Amount per layer (max):	50ml/m ²
Total application volume:	15-50 ml/m ²
Drying:	15 mins - to touch
Finishing:	Allow 24 hours of drying time before applying other techniques or products
Sealing:	After 24 hours, apply any Jax Sealers if desired for extra protection on high traffic areas like floor, table tops, vanities, kitchen counter

PROCESSING & SPECIAL NOTES

Processing Instructions:	Apply the Jax Oleum directly onto the wood or onto your rag and rub it into the wood. Once evenly spread over the wood, remove any excess Jax Oleum. Once the oil has absorbed into the top layer of the wood, no more will be absorbed.
Particular Instructions:	Remove any excess Oleum to avoid a sticky finish.

GENERAL WORKMANSHIP NOTES

General Instruction on Workmanship:	Softer woods will absorb more Oleum, harder woods will absorb less. Colour will vary on different wood species. Do not use a sponge. Soak used rags/cloths after applying the Jax Oleum in a bucket of water before discarding them, to avoid spontaneous combustion.
-------------------------------------	---

Our technical information is continually adapted to keep up to date with the latest technology and statutory regulations. The indicated values are no specification, but typical product data. The latest version is always available online at www.jaxoleum.co.za or talk to your local account manager. This information is for advice and is based on the best knowledge available and careful research in line with the current state of the art. This information cannot be held as legally binding. We also refer you to our terms and conditions of business. Material safety data sheet is provided in accordance with EC regulation no. 1907/2006.